

Restrictors and Ancillary window devices

ancillary window devices

Distributed by



Unit 210 Holly Road, Western Ind. Estate, Naas Road, Dublin 12. Ph 01-4565170 Fx 014502371 Email info@nationalseal.ie Web: www.nationalseal.ie Nico produces a selection of ancillary devices to be used with its range of window products – suitable for PVC-u, timber and aluminium profiles.

restrictor safety catch

The Nico Restrictor
Safety Catch is a
simple way to limit
window opening to
100mm in compliance
with BS EN 143511:2006. Ideal for new
or retrofit installations.



x-tra bolt

The Nico X-tra Bolt provides additional security for the hinge side of windows to meet the requirements of BS7950. 'Secured by Design' and BBA approved.



restrictor arm

UK manufacture

Easy and simple to fit

Suitable for PVC-u,
timber & aluminium
profiles

Complement Nico range of Window Hinges

10 year guarantee

BBA approved (X-tra Bolt)

The Nico Restrictor
Arm permanently
restricts the opening of
windows and doors for
added safety.
Available in three
sizes, it is Ideal for
large window sashes
and French Doors.





Fitting Instructions

RESTRICTOR SAFETY CATCH

Secure the restrictor safety catch arm assembly to the sash using the same location groove as hinge, ensuring that the hook is facing towards you.

Position the striker plate on the frame using the same location groove as hinge channel, ensuring that striker pin locates fully in hook feature when opened.

Check opening does not exceed 100mm maximum. If a smaller opening is required, position catch further away from the hinge. For a larger opening, position catch closer to the hinge. NOTE. 100mm maximum must not be exceeded.

RESTRICTOR ARM

With the door or window open to 90° , fit channel to frame so that the friction arm engages on the frame at a 45° angle (drawing available on request).

X-TRA BOLT SECURITY BOLT

The X-tra Bolt is simply installed by fixing one half of the Bolt to the frame 50-100mm above the Friction Hinge nose cap and fixing the other half opposite to it on the sash.

The X-tra Bolt should be fixed into window reinforcement if possible. If not, fix to the frame with 4.8mm screws.

Secured by Design





Distributed by




Unit 210 Holly Road, Western Ind. Estate, Naas Road, Dublin 12. Ph 01-4565170 Fx 014502371 Email info@nationalseal.ie Web: www.nationalseal.ie


ancillary devices

Technical Data

Restrictor Safety Catch



Restrictor Arm



X-tra Bolt Security Bolt

