

Unit 210 Holly Road, Western Industrial Estate. Naas Road, Dublin 12 Ph 00353-1-4565170 Fax 00353-1-4502371 Email: info@nationalseal.ie web: www.nationalseal.ie

# Winkhaus OBV Safety Catch Restrictors Restrictors for PVCu and Timber Windows





# Winkhaus OBV Safety Catch Restrictor

Restrictors for PVCu and Timber Windows



## **OBV Safety Catch Features**

- 5 screws- 3 easy steps
- Restricts opening to 50mm 100mm
- Push button release
- Non-locking and Grub screw locking options available
- Automatically restricts window opening
- Perfect for retrofitting to existing windows
- Available in White or brown

### **OBV Safety Catch Restrictor**

The Winkhaus OBV Safety Catch and OBVA (grub screw locking) are a family of window restrictors, which are designed to help prevent small children opening windows fully and falling out.

An extensive range of angle packers is available to allows the OBV Safety Catch Restrictor to be fitted to PVCu windows.



#### Key features:

The robust design incorporates the following features:

- The OBV automatically prevents the opening of a window greater than 50mm · 100mm (depending on the positioning on the window).
- The OBV locking bar can be released for full opening of the sash by keeping the push button depressed.
- The OBV will automatically re-engage when the window is closed.
- Surface mounted vertically or horizontally on both outward opening and inward opening windows, it can be retrofitted to existing windows as an additional security and safety device.
- 3mm adjustment of steel hook possible for correct operation.
- Easily fitted using 5 screws. The steel hook is fixed with three screws (for PVCu windows fixing into reinforcement is recommended). Drill jigs available for both site fixing or factory fixing.
- An extensive range of packers and mounting blocks available
- 1mm shims available for optimum positioning of steel hook.
- Purpose designed to provide high levels of child safety and increased security for both new and existing windows, together with a lockable 50mm vent position.
- Can be fitted by eye utilising aligning mark on body of Safety Catch. The line can be transfered using a pencil to indicate the postion for the hook base plate.
- The OBV is available in white and brown as standard.

